



PRODUCT SPECIFICATIONS

Size 7x48in
Thickness 2.5 mm
Wear Layer 12 mil

Pattern Repeat Wood Pattern

Micro-Beveled No

Class/ASTM F1700 Class III Printed Film/Vinyl Plank—Type B (embossed)

Backing Class Commercial Grade

Gloss Level 7-10

Traffic Use Commercial

FloorScore Certified Yes

Backstamp Info None

WARRANTY

7-year Commercial

Wear-through / manufacture defects

PERFORMANCE

ASTM F2055 Size and Tolerance Pass As specified 0.016 in / lin ft
ASTM F386 Thickness Pass As specified 0.005 in / lin ft

ASTM F2055 Squareness Pass Maximum 0.010 in
ASTM F1914 Residual Indentation Pass Average < 8%

ASTM F137 Flexibility Passes 6mm mandrel / no crack or break

ASTM F2199 Dimensional Stability

ASTM F925 Chemical Resistance

ASTM F1514 Resistance to Heat

ASTM F1515 Resistance to Light

ASTM F1515 Resistance to Light

ASTM E648 Critical Radiant Flux

Pass 0.011 in / ft < 0.020 in / ft

Pass No change / slight change

Pass < 8 (delta E) average

Class 1 (< 0.45 w/cm2)

ASTM E662 Optical Smoke Density Passes <450

ASTM C1028 Slip Resistance Pass ADA Compliant (> 0.50)
ASTM F970 Static Load Pass 1000 psi / 250 psi (< 0.005 in)



by **OSCS**certified.

