



PRODUCT SPECIFICATIONS

Size 7x48in
Thickness 3 mm

Wear Layer 0.51 mm/ 20 mil
Pattern Repeat Wood Pattern

Micro-Beveled No

Class/ASTM F1700 Class III Printed Film/Vinyl Plank—Type B (embossed)

Backing Class Commercial Grade

Gloss Level 7-10

Traffic Use Heavy Commercial

FloorScore Certified Yes

Backstamp Info None

WARRANTY

15-year Commercial

Wear-through / manufacture defects

PERFORMANCE

ASTM F2055 Size and Tolerance Pass As specified 0.016 in / lin ft

ASTM F386 Thickness Pass As specified 0.005 in / lin ft

ASTM F2055 Squareness Pass Maximum 0.010 in
ASTM F1914 Residual Indentation Pass Average < 8%

ASTM F137 Flexibility Passes 6mm mandrel / no crack or break

ASTM F2199 Dimensional Stability Pass 0.011 in / ft < 0.020 in / ft ASTM F925 Chemical Resistance Pass No change / slight change

ASTM F1514 Resistance to Heat Pass < 8 (delta E) average
ASTM F1515 Resistance to Light Pass < 8 (delta E) average
ASTM E648 Critical Radiant Flux Class 1 (< 0.45 w/cm2)

ASTM E662 Optical Smoke Density Passes <450

ASTM C1028 Slip Resistance Pass ADA Compliant (> 0.50)

ASTM F970 Static Load Pass 1000 psi / 250 psi (< 0.005 in)



- CSCScortified

