



# TITAN

## Waterproof TriCore

### PRODUCT SPECIFICATIONS

---

|                    |                                    |
|--------------------|------------------------------------|
| Size               | 7" x 48"                           |
| Thickness          | 4.4 mm                             |
| Wear Layer         | 12 mil                             |
| Finish             | ArmourGuard Microbead Technology   |
| Attached Pad       | Quiet Step Cushion                 |
| Micro Beveled      | Yes                                |
| Edge Traffic Use   | Light Commercial                   |
| Installation       | Floating Click                     |
| Pieces Per Carton  | 16                                 |
| SF Per Carton      | 38.45                              |
| Cartons Per Pallet | 60                                 |
| SF Per Pallet      | 2,307                              |
| Material           | 100% Virgin / Ortho-Phthalate Free |

### WARRANTY

---

12 Year Light Commercial / Limited Residential Lifetime

### PERFORMANCE

---

|                                  |  |
|----------------------------------|--|
| ASTM F2055 Size                  | Pass   |
| ASTM F386 Thickness              | Pass   |
| ASTM F2055 Squareness            | Pass   |
| ASTM F1914 Residual Indentation  | Pass   |
| ASTM F137 Flexibility            | Pass   |
| ASTM F2199 Dimensional Stability | Pass   |
| ASTM F925 Chemical Resistance    | Pass   |
| ASTM F1514 Resistance to Heat    | Pass   |
| ASTM F1515 Resistance to Light   | Pass   |
| ASTM F 970 Static Load Limit     | Pass   |
| Certified Low Emitting Product   | Meets Guidelines   |
| Indoor Air Quality               | Meets Guidelines   |
| Indoor Sound Transmission Test   | IIC: 68 (test condition: 6" concrete slab with drop ceiling) |

