



PRODUCT SPECIFICATIONS

| Size | 12" x 24" | |
|--------------------|----------------------------------|--|
| Thickness | 6.5 mm | |
| Wear Layer | 20 mil | |
| Finish | DiamondGuard / HealthGuard | |
| Attached Pad | QuietStep Cushion+tm | |
| Material | Waterproof TriCore tm | |
| Micro Beveled Edge | Yes | |
| Traffic Use | Light Commercial | |
| Installation | Floating Click | |
| Pieces Per Carton | 12 | |
| SF Per Carton | 24.03 | |
| Cartons Per Pallet | 48 | |
| SF Per Pallet | 1,153.44 | |

WARRANTY

15 Year Light Commercial / Limited Lifetime Residential

PERFORMANCE

| ASTM F2055 Size | Pass | |
|----------------------------------|---|----------------------------------|
| ASTM F386 Thickness | Pass | |
| ASTM F2055 Squareness | Pass | |
| ASTM F1914 Residual Indentation | Pass | |
| ASTM F137 Flexibility | Pass | |
| ASTM F2199 Dimensional Stability | Pass | |
| ASTM F925 Chemical Resistance | Pass | |
| ASTM F1514 Resistance to Heat | Pass | |
| ASTM F1515 Resistance to Light | Pass | A1117. |
| ASTM F 970 Static Load Limit | Pass | floor |
| Certified Low Emitting Product | Meets Guidelines | score |
| Indoor Air Quality | Meets Guidelines | Contraction of the second second |
| Indoor Sound Transmission Test | IIC: 68 (test condition: 6"concrete slab with drop ceiling) | by OSCScertified . |
| | | |