



## **PRODUCT SPECIFICATIONS**

Size	7" x 48"	
Thickness	5.5 mm	
Wear Layer	20 mil	
Finish	DiamondGuard / HealthGuard	
Attached Pad	QuietStep Cushion+tm	
Material	Waterproof TriCore <sup>tm</sup>	
Micro Beveled Edge	Yes	
Traffic Use	Light Commercial	
Installation	Floating Click / Unilin	
Pieces Per Carton	12	
SF Per Carton	28.837	
Cartons Per Pallet	45	
SF Per Pallet	1,297.67	

## WARRANTY

15 Year Light Commercial / Limited Lifetime Residential

## PERFORMANCE

ASTM F2055 Size	Pass	
ASTM F386 Thickness	Pass	
ASTM F2055 Squareness	Pass	
ASTM F1914 Residual Indentation	Pass	
ASTM F137 Flexibility	Pass	
ASTM F2199 Dimensional Stability	Pass	
ASTM F925 Chemical Resistance	Pass	
ASTM F1514 Resistance to Heat	Pass	
ASTM F1515 Resistance to Light	Pass	A111.
ASTM F 970 Static Load Limit	Pass	floor
Certified Low Emitting Product	Meets Guidelines	score
Indoor Air Quality	Meets Guidelines	······································
Indoor Sound Transmission Test	IIC: 68 (test condition: 6"concrete slab with drop ceiling)	by <b>OSCScertified</b> .