



PRODUCT SPECIFICATIONS

Size	9" x 72"
Thickness	5.5 mm
Wear Layer	20 mil
Finish	DiamondGuard™ / HealthGuard™
Attached Pad	QuietStep Cushion+
Material	Waterproof TriCore™
Micro Beveled Edge	Yes
Traffic Use	Light Commercial / Residential
Installation	Floating Click / Unilin
Pieces Per Carton	8
SF Per Carton	36.64
Cartons Per Pallet	48
SF Per Pallet	1,758.52

WARRANTY

15 Year Light Commercial / Limited Lifetime Residential

PERFORMANCE

ASTM F2055 Size	Pass
ASTM F386 Thickness	Pass
ASTM F2055 Squareness	Pass
ASTM F1914 Residual Indentation	Pass
ASTM F137 Flexibility	Pass
ASTM F2199 Dimensional Stability	Pass
ASTM F925 Chemical Resistance	Pass
ASTM F1514 Resistance to Heat	Pass
ASTM F1515 Resistance to Light	Pass
ASTM F 970 Static Load Limit	Pass
Certified Low Emitting Product	Meets Guidelines
Indoor Air Quality	Meets Guidelines
Indoor Sound Transmission Test	IIC: 68 (test condition: 6" concrete slab with drop ceiling)