



Soma(T)

LUXURY VINYL TILE

PRODUCT SPECIFICATIONS

| | |
|----------------------|--|
| Size | 36"x36" (T90, T91) |
| Thickness | 3.0 mm |
| Wear Layer | 20 mil |
| Finish | DiamondGuard™ / HealthGuard™ |
| Micro Beveled Edge | No |
| Traffic Use | Heavy Commercial |
| Installation | Direct Glue |
| Recommended Adhesive | SAR 5000 (Pressure Sensitive Adhesive) |
| Pieces Per Carton | 6 |
| SF Per Carton | 54 |
| Cartons Per Pallet | 35 |
| SF Per Pallet | 1,890 |
| Material | 100% Virgin |

WARRANTY

15 Year Commercial / 20 Year Residential

PERFORMANCE

| | |
|----------------------------------|--|
| ASTM F2055 Size and Tolerance | Pass As specified 0.016 in / lin ft |
| ASTM F386 Thickness | Pass As specified 0.005 in / lin ft |
| ASTM F2055 Squareness | Pass Maximum 0.010 in |
| ASTM F1914 Residual Indentation | Pass Average < 8% |
| ASTM F137 Flexibility | Passes 6mm mandrel / no crack or break |
| ASTM F2199 Dimensional Stability | Pass 0.011 in / ft < 0.020 in / ft |
| ASTM F925 Chemical Resistance | Pass No change / slight change |
| ASTM F1514 Resistance to Heat | Pass < 8 (delta E) average |
| ASTM F1515 Resistance to Light | Pass < 8 (delta E) average |
| ASTM E648 Critical Radiant Flux | Class 1 (< 0.45 w/cm2) |
| ASTM E662 Optical Smoke Density | Passes <450 |
| ASTM C1028 Slip Resistance | Pass ADA Compliant (> 0.50) |
| ASTM F970 Static Load | Pass 1000 psi / 250 psi (< 0.005 in) |



by SCS certified



PRODUCT SPECIFICATIONS

| | |
|----------------------|--|
| Size | 18"x 36" (T92, T93, T94) |
| Thickness | 3.0 mm |
| Wear Layer | 20 mil |
| Finish | DiamondGuard™ / HealthGuard™ |
| Micro Beveled Edge | No |
| Traffic Use | Heavy Commercial |
| Installation | Direct Glue |
| Recommended Adhesive | SAR 5000 (Pressure Sensitive Adhesive) |
| Pieces Per Carton | 10 |
| SF Per Carton | 45 |
| Cartons Per Pallet | 35 |
| SF Per Pallet | 1,890 |
| Material | 100% Virgin |

WARRANTY

15 Year Commercial / 20 Year Residential

PERFORMANCE

| | |
|----------------------------------|--|
| ASTM F2055 Size and Tolerance | Pass As specified 0.016 in / lin ft |
| ASTM F386 Thickness | Pass As specified 0.005 in / lin ft |
| ASTM F2055 Squareness | Pass Maximum 0.010 in |
| ASTM F1914 Residual Indentation | Pass Average < 8% |
| ASTM F137 Flexibility | Passes 6mm mandrel / no crack or break |
| ASTM F2199 Dimensional Stability | Pass 0.011 in / ft < 0.020 in / ft |
| ASTM F925 Chemical Resistance | Pass No change / slight change |
| ASTM F1514 Resistance to Heat | Pass < 8 (delta E) average |
| ASTM F1515 Resistance to Light | Pass < 8 (delta E) average |
| ASTM E648 Critical Radiant Flux | Class 1 (< 0.45 w/cm2) |
| ASTM E662 Optical Smoke Density | Passes <450 |
| ASTM C1028 Slip Resistance | Pass ADA Compliant (> 0.50) |
| ASTM F970 Static Load | Pass 1000 psi / 250 psi (< 0.005 in) |



by SCS certified.