

Waterproof TriCore

PRODUCT SPECIFICATIONS

Size 7" x 48"

Thickness 4.5 mm

Wear Layer 12 mil

Finish DiamondGuard™ / HealthGuard™

Attached Pad QuietStep Cushion™

Micro Beveled Yes

Edge Traffic Use Light Commercial
Installation Floating Click / Unilin

Pieces Per Carton 16
SF Per Carton 38.45
Cartons Per Pallet 45

SF Per Pallet 1,730.25

Material Waterproof TriCore[™] / 100% Virgin

WARRANTY

12 Year Light Commercial / Limited Lifetime Residential

PERFORMANCE

ASTM F2055 Size **Pass** Pass ASTM F386 Thickness **ASTM F2055 Squareness Pass** ASTM F1914 Residual Indentation Pass Pass ASTM F137 Flexibility **ASTM F2199 Dimensional Stability** Pass **ASTM F925 Chemical Resistance** Pass ASTM F1514 Resistance to Heat **Pass** ASTM F1515 Resistance to Light **Pass** ASTM F 970 Static Load Limit Pass

Certified Low Emitting Product Meets Guidelines
Indoor Air Quality Meets Guidelines

Indoor Sound Transmission Test IIC: 68 (test condition: 6" concrete

slab with drop ceiling)









